

# ProCash 1500xe weatherized

Monofunction cash dispenser  
for through-the-wall installations



Compact design,  
minimal footprint

Bundle output  
of up to 60 notes

Optimized cash  
management

Two frame  
variants

Flexible deploy-  
ment, inclusive  
off-premise

Comprehensive  
security solutions

Open hardware  
and software  
architectures

Project-specific  
solutions



## Technical Data

# ProCash 1500xe weatherized

## Monofunction cash dispenser

The ProCash 1500xe weatherized is a model of the ProCash 1500xe and therefore comes with the familiar capacity and reliability that this family offers. The rearload-system can be installed flexibly in outdoor environments where space is limited and a moderate climate predominates (see temperature specifications), whether at a bank branch or off premises.

Two specially sealed frame variants of 45 mm and 180 mm are available for through-the-wall installation and cover a wide variety of site requirements. An integrated lighted logo display area draws attention to the automated teller machine and lighting for the customer panel improves convenience in the dark.

### DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- 12.1" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

### KEYBOARD

- Encrypting PIN pad (EPP V5) with 4 function keys
- PIN shield (VISA-compliant)

### CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06
- Various card retract compartments

### CASH DISPENSING

- Up to 4 cassettes (sealable)
- Max. filling height per cassette: 310 mm
- Note reject/bundle retract, storage in separate compartments
- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

### SECURITY

- Intruder alarm
- Portrait camera
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

### SAFES

- UL 291 Level 1

### PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

### MARKETING FEATURES

- Lighted logo display area in frame
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

### AUDIO

- Headset jack

### OPERATING SYSTEM

- Windows XP

### APPLICATION SOFTWARE

(multivendor and multichannel)

- ProClassic
- ProClassic/Enterprise

### POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

### TEMPERATURE RANGE

- + 5° C to + 40° C
- Customer panel vicinity - 15° to + 40° C (with heating)

### RELATIVE HUMIDITY

- 5% to 85%

### INSTALLATION

- Rearload
- Semi-outdoor environment
- 2 frame variants (both normal steel): 45 mm (e.g. for glass walls) 180 mm (see picture on front page)

### APPROVALS (IN PREPARATION)

