

ProCash 2250xe

Multifunction ATM for outdoors,
drive-up model

In addition to its basic functions of dispensing cash and displaying information, the ProCash 2250xe can be extended to meet a financial institution's specific requirements.

- Load/unload electronic purse
- Print receipts or other documents with a full-graphics printer
- Issue tickets or vouchers from versatile cassettes
- Print statements or other information up to a paper width of 250 mm / 9,84 in.
- Deposit banknotes/valuable documents in envelopes

Features and highlights

- Rearload system, through-the-wall installation with walls up to 220 mm / 8,66 in thick
- Compact size
- Standard PC with Pentium IV
- Output of bundles of up to 60 notes
- Sunlight LCD (12.1") with autoscaling function
- Climate control unit for installation outdoors
- EMV 2000-certified
- Optical indicators at all input and output modules
- Options: custom colors, labeling in braille, energy-saving function



■ The ProCash 2250xe has been developed specifically for use from cars. The system is installed through the wall. A climate control unit that is available as an option ensures availability even in the harshest weather conditions. This system has an extremely low depth and can be installed at locations where space is limited.

ProCash 2250xe

The new "xe-generation"

Further development of Wincor Nixdorf's ProCash product family has resulted in the "xe-generation", which has been optimized technologically to address international customer requirements and trends while retaining its external appearance and overall functionality. The flexibility of these systems is unrivaled on the market when it comes to ideal configuration and availability.

TECHNICAL DATA

SYSTEM CONTROL

Standard PC

DISPLAY

The various VGA, SVGA and XGA resolutions can be implemented on a single display thanks to the autoscaling function.

- 12.1" TFT LCD sunlight

OPTIONS

- Touchscreen
- Privacy display filter

Published by
Wincor Nixdorf International GmbH
Heinz-Nixdorf-Ring 1
D-33106 Paderborn
Germany
Phone +49 (0) 52 51/693-3301
Fax +49 (0) 52 51/693-5918
<http://www.wincor-nixdorf.com>

© **Wincor Nixdorf International GmbH**

ProCash[®] is a registered trademark of Wincor Nixdorf International GmbH

All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Delivery subject to availability, subject to change for technical reasons.

Order No. **R10140-J-Z744-1-7600**
Printed in Germany, October 2002

KEYBOARD

- 8 stainless steel softkeys
- Numeric keypad including 4 function keys

OPTIONS

- Encrypting PIN pad (EPP)
- Encryption/decryption module (EDM)
- Braille labeling

ELECTRONIC PURSE

Loading and unloading of electronic purses (transaction module for the German GeldKarte)

CARD HANDLING

- Hybrid card reader (motorized)
- EMV 2000-certified
- Tamperproof card slot
- Card retained if not removed, returned in case of power failure

OPTIONS

- CIM 86 and/or MM (preparation)
- Different card retract boxes

CASH DISPENSING

- 1 to 4 cassettes (sealable as standard)
- Max. filling height per cassette: 310 mm / 12,20 in.
- Single reject/bundle retract, storage in separate compartments

OPTIONS

- Cassette with lock
- Cassette with low cash sensor
- Cassette pre-setting

SECURITY

SAFES

- UL 291 Level 1

OPTIONS

- Intruder alarm system
- Portrait camera
- Uninterruptible power supply

OPTIONS

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)
- Statement printer (dot matrix or thermal)

ENVELOPE DEPOSIT

- Integrated envelope dispenser
- Single line printing of transaction data
- Capacity: up to 200 or 300 envelopes, depending on the deposit box, special security box as an option

CHECK PROCESSING

- Scanning module for individual checks or other inpayment documents

MISCELLANEOUS

- Lighted logo area
- Info panel for card symbols
- Loud speakers and/or headset
- Climate control unit (heating)

OPERATING SYSTEM

- Windows NT
- Windows XP

APPLICATION SOFTWARE

- ProClassic
- IBM 473x/PBM Emulation
- NDC (NCR Direct Connect)
- DDC (Diebold Direct Connect)

POWER SUPPLY

110 - 120 V~/ 220 - 240~, 50 - 60 Hz

ENVIRONMENTAL CONDITIONS

- Without climate control unit:
Temperature: +5° C to +40° C
(+41° F to +104° C)
- With climate control unit:
Temperature: - 40° C to +50° C
(-40° F to +122° F)
(Customer panel)
- Relative humidity: 5% to 85%

COMPLIANCE WITH STANDARDS

