

# ProCash 2350xe

Multifunction ATM

Freestanding island drive-up system

**The ProCash 2350xe** is the latest addition to the ProCash product family, rounding off Wincor Nixdorf's line of solutions for drive-up banking. It withstands extreme climate conditions while addressing international customer requirements and trends. The clear layout of all the customer controls complies with ergonomic requirements and allows mobile customers to handle their banking business fast and conveniently without leaving their cars.

**In addition to** its basic functions of dispensing cash and displaying information, ProCash 2350xe can be extended with additional functions to meet the specific requirements of individual banks:

- Automated bulk cash and check deposit (Cash/Check Deposit Module)
- Envelope deposit for banknotes, checks, etc.
- Print statements or other information up to a paper width of 250 mm
- Print receipts or other documents with the fully graphics-capable printer
- Dispense tickets or vouchers from the versatile cassettes
- Audio systems (loudspeakers/headset)
- Load/unload electronic purse



■ The island drive-up system ProCash 2350xe guarantees 7 x 24 hour service even in the most rugged environments. Equipped as standard with sunlight-viewable screens, durable materials and a broad array of security options, it complies with the enhanced standards that apply to fully stand-alone ATMs. The freestanding drive-up system also offers an optional function for automated bulk banknote and check deposits.

# ProCash 2350xe

## Features and highlights

- Made of highly specialized durable materials that withstand vandalism and all climatic conditions
- Climate control unit for extreme temperature ranges
- Different security features for special environments
- Ergonomic design for easy use from all kinds of vehicles
- Freestanding frontload system for ease and speed of serviceability
- Fits standard 42" islands
- Standard PC with Pentium IV
- Card readers are EMV 2000-certified
- 12.1" sunlight-readable LCD screen with autoscaling functionality as standard
- Issues bundles of up to 60 banknotes
- Lighted indicators at all input and output modules, labeling in Braille

## TECHNICAL DATA

### SYSTEM CONTROL

Standard PC

### DISPLAY

The various VGA, SVGA and XGA resolutions can be implemented on a single display thanks to the autoscaling function.

- 12.1" sunlight-viewable TFT LCD

### DISPLAY OPTIONS

- Touchscreen
- Privacy display filter

Published by

**Wincor Nixdorf International GmbH**

Heinz-Nixdorf-Ring 1

D-33106 Paderborn

Germany

Phone +49 (0) 52 51 / 6 93-33 01

Fax +49 (0) 52 51 / 6 93-59 18

info.banking@wincor-nixdorf.com

[www.wincor-nixdorf.com](http://www.wincor-nixdorf.com)

© Wincor Nixdorf International GmbH

ProCash® is a registered trademark of Wincor Nixdorf International GmbH.

All rights, including rights created by patent grant or registration of a utility model or design, are reserved.

Delivery subject to availability, subject to change for technical reasons.

Order No. **R10141-J-Z744-1-7600**

Printed in Germany, Februar 2006, S

## KEYBOARD

- 8 softkeys made of stainless steel
- Numeric keypad including 4 function keys

## KEYBOARD OPTIONS

- Encrypting PIN Pad (EPP)
- Privacy visor (from middle of 2006)
- Labeling in Braille

## ELECTRONIC PURSE

- Load/unload electronic purse (transaction module for Germany's GeldKarte)

## CARD HANDLING

- Hybrid card reader (motorized)
- EMV 2000-certified
- Tamperproof card slot
- Card retained if not removed
- Card returned in case of power failure

## CARD HANDLING OPTIONS

- DIP reader
- DIP hybrid reader
- CIM 86 preparation
- Different card retract boxes

## CASH DISPENSING

- 2 or 4 cassettes (sealable as standard)
- Max. filling height per cassette: 12.20" (310 mm)
- Single reject/bundle retract, storage in separate compartments

## CASH DISPENSING OPTIONS

- Cassette with lock
- Cassette with low cash sensor
- Cassette pre-setting

## SECURITY

### SAFES

- UL 291 Level 1 safe

### SECURITY OPTIONS

- Intruder alarm system
- Portrait camera
- Uninterruptible power supply
- Protection against intrusion mechanisms at card entry slot
- Anti-skimming device
- Anti-Lebanese loop card reader
- Ink staining

## OPTIONS

### PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)
- Statement/information printer (dot matrix or thermal)

### ENVELOPE DEPOSIT

- Integrated envelope dispenser
- Single line printing of transaction data
- Capacity: up to 200 or 300 envelopes, depending on the deposit box, special security box as an option

### CASH/CHECK DEPOSIT MODULE

- Cash Deposits
  - 1 or 2 cash cassettes each with a capacity of 2000 notes
  - No. of notes per bundle: 50
  - Separate compartment for counterfeit notes
- Check Processing
  - Scanning module for check bundle
  - 1 or 2 check cassettes each with a capacity of 2000 checks
  - No. of checks per bundle: 50

## MISCELLANEOUS

- Lighted logo area
- Lighted indicators at all input and output modules
- Info panel for card symbols
- Loudspeaker and/or headset plug
- Climate control unit, air conditioning as standard

## OPERATING SYSTEM

- Windows XP

## APPLICATION SOFTWARE

- ProClassic
- IBM 473x/PBM Emulation
- NDC (NCR Direct Connect)
- DDC (Diebold Direct Connect)

## POWER SUPPLY

110 – 120 V~/220 – 240 V~, 50 – 60 Hz

## ENVIRONMENTAL

### TEMPERATURE RANGE

- -30° F to 122° F (-40° C to 50° C)

### RELATIVE HUMIDITY

- 5% to 85%

## APPROVALS

